

→ HIGH-CAPACITY SHREDDERS **IDEAL 4605**

COMPACT SHREDDER WITH FEEDING HOPPER FOR CENTRALISED USE

Tilting feeding hopper for crumpled paper | feeding paddle for effective insertion of crumpled paper into the cutting head | second feed opening located under the hopper for flat paper and computer printouts with automatic start/stop via a photo cell | fold-away feeding table | main switch and emergency cut-off switch | electronically controlled automatic reverse and power cut-off in case of overfeeding | soft touch keys for forward (continuous operation), stop and reverse | optical indicators for the operational status of the machine | robust shredding heads with special hardened cutting shafts made of high-quality steel, resistant against soft metal objects | 5 years guarantee on the cutting shafts | powerful 2.2 kW three phase motor with thermal motor protection | front door and mobile shred bin for easy removal of the full shred bag | high volume container of 230 litres for the shredded material | automatic stop when hopper or front door is opened, or when the shred bin is full | mobile on castors

Power connection²: 400 V / 50 Hz / 3~, Dimensions (H x W x D): 1700 x 740 x 765 mm, Weight: 256 kg.



L.T.E. Listed 802 D

FEEDING HOPPER



Should a paper jam occur, the electronically secured feeding hopper can be tilted for safe and convenient clearing.

MOBILE SHRED BIN



The shred bin on castors is easily removable through the front door. The shredder stops automatically if the door is opened.

→ IDEAL 4605

Cutting width	6 mm
Sheet capacity ¹	90-100 75-85
Security level	2
Feed opening	460 mm
Motor capacity	2.2 kW

→ IDEAL 4605-C/C

Particle size	4 x 60 mm
Sheet capacity ¹	65-70 55-60
Security level	3
Feed opening	460 mm
Motor capacity	2.2 kW

→ IDEAL 4605-C/C

Particle size	2 x 15 mm
Sheet capacity ¹	35-40 29-34
Security level	4
Feed opening	460 mm
Motor capacity	2.2 kW

¹ A4 paper, 70 g/m² | 80 g/m²

² other voltages available